

REPORT DOCUMENTATION PAGE

Form Approved OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE 25 June 1997	3. REPORT TYPE AND DATES COVERED Final Report	
4. TITLE AND SUBTITLE Spatial and Energetic Characterization of X-Ray Emission from Inverse Capillary Discharges			5. FUNDING NUMBERS F6170896W0193	
6. AUTHOR(S) Dr. Mihai Ganciu-Petcu				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Institute of Atomic Physics P.O. Box MG-4 Bucharest 76900 Romania			8. PERFORMING ORGANIZATION REPORT NUMBER N/A	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) EOARD PSC 802 BOX 14 FPO 09499-0200			10. SPONSORING/MONITORING AGENCY REPORT NUMBER SPC 96-4040	
11. SUPPLEMENTARY NOTES				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.			12b. DISTRIBUTION CODE A	
13. ABSTRACT (Maximum 200 words) This report results from a contract tasking Institute of Atomic Physics as follows: The contractor will investigate several questions associated with pumping without inversion as described in his proposal.				
14. SUBJECT TERMS Physics, Lasers			15. NUMBER OF PAGES 5	
			16. PRICE CODE N/A	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL	

NSN 7540-01-280-5500

Standard Form 298 (Rev. 2-89)
Prescribed by ANSI Std. Z39-18
298-102

DTIC QUALITY INSPECTED 3**19980223 076**

1

**Institute of Atomic Physics
National Institute for Laser, Plasma and Radiation Physics**

P.O. Box MG-36, Bucharest, ROMANIA, Fax: 40-1-420-9101

FAX: Number of pages including this one: 5

SUBJECT: Contract F61708-96-W0193 (Special Project SPC-96-4040)
DATE: 25 June, 1997

TO: **Dr. Weldon E. Corley**
603 Contracting Flight
Bldg 202, Room 217
RAF Crought, NORTHANTS
United Kingdom, NN13 5NQ
Fax: 44-1280-708-333

FROM: **Dr. Mihai Ganciu-Petcu**
Institute of Atomic Physics
National Institute for Laser, Plasma and Radiation Physics
Low Temperature Plasma Department (Lab. 26)
P.O.Box MG-36, Magurele, Bucharest, ROMANIA
Fax: 40-1-420-9101
E-mail: ganciu@roifa.ifa.ro

Dear Dr. Corley,

Please find enclosed my final report on "Spatial and energetic characterization of x-ray emission from inverse capillary discharges", contract F61708-96-W0193.

Yours most sincere

Mihai Ganciu-Petcu

DTIC QUALITY INSPECTED 3

Phase 1 Basic Research on Induced Gamma Emission (IGE)

Contract F61708-96-W0193

Final report

Submitted by: Mihai GANCIU-PETCU
PhD, Senior Researcher

Address: Institute of Atomic Physics
National Institute for Laser, Plasma and Radiation Physics
Low Temperature Plasma Department
P.O.Box MG-36, Bucharest, ROMANIA
Fax: 40-1-420 9101, E-mail: ganciu@roifa.ifa.ro

Title of Research: **SPATIAL AND ENERGETIC CHARACTERIZATION OF
X-RAY EMISSION FROM INVERSE CAPILLARY
DISCHARGES**

Depletion of certain K-quantum number nuclear isomers such as ^{178}Hf may be achieved by up-conversion with relatively "soft" photons, having an energy of the order of tens to hundreds keV [1]. In this case the use of less expensive, tunable, lightweight X-ray machines becomes possible.

Recently, a X-ray generator providing an optimum coupling of the radiation to the active medium has been proposed. The X-rays are produced by bremsstrahlung of an intense pulsed electron beam [2, 3] cruising along the surface of a dielectric fiber (Cruise Effect) [4].

The main source of hard X rays in wall assisted discharge is the bremsstrahlung following the fast electron interaction with the walls. When the diameter of the discharge tube shrinks, one speaks about capillary discharges. While for capillaries the discharge is assisted by the capillary dielectric walls, in the case of the "Cruise Effect" (CE) the discharge is mainly assisted by an axial dielectric fiber. Consequently, we may call this system an "inverse capillary discharge"[5].

One important advantage of inverse capillary discharges is the possibility to use also the ablation plasma from the fiber surface for a better cruising of the beam. In contrast, in the case of capillary discharges, the ablation from the internal surface of the capillary determines the detachment of the electron beam from the wall and the collapsing of the channel plasma on the axis [6].

The CE can be described qualitatively by extending the ion trap model [7] of the pulsed electron beam produced in pseudospark-like discharges [8,9]. Thus, when the dielectric fiber is absent, the exceptional radial stability along many centimeters of the electron beam described in [2,3,7] is the result of counterbalancing of the Lorentz and electrostatic forces. Under steady state conditions this implies the well-known equilibrium condition:

$$n_i(x,t) = n_e(x,t)[1 - v_e^2(x,t)/c^2]$$

Here n_e and v_e stand for the electron density and velocity, respectively, at the distance x along the beam axis and at the moment t of the discharge. This equation has been deduced by assuming a homogeneous current tube and n_i denotes an effective ion density accounting for the existence of multiply charged ions [7].

Since our beam currents are below the Alfvén limit, for the slow electrons the magnetic force is small and these electrons are expelled from the axial region. Consequently, the electron

beam becomes surrounded by a thin layer of positive charge which ensures the vanishing of the electric field at the limit of the neutral plasma. The fast electrons which lose energy by collisions are still kept along the beam by the radial potential pockets due to this double layer and eventually regain energy from the axial electric field, while the secondary electrons are rapidly removed. On the other hand, the potential seen by the ions looks rather like a simple potential well, whose characteristics were inferred in [7] under the assumption of a uniform initial radial ion density and a constant electron density. For typical conditions of our experiment, in spite of the high electron space charge in which the ions are embedded during the discharge, the recombination is prohibited due to the velocity mismatch between the electrons and the ions.

The presence of the dielectric fiber can be modeled by a layer of positive charge along its surface [5]. The electric field in the proximity of the fiber is attracting the electrons in the beam. As a result, the beam is captured by the fiber and is "dressing" it. The ions in the beam, although repelled by the fiber, have enough kinetic energy in the potential well to be able to deposit on the fiber, in a dynamic equilibrium with the electrons which tend to neutralize it.

Together with the dependence on the pressure, voltage and geometrical configuration of the discharge, the X-ray emission by CE is currently investigated as a function of the dielectric material, and of its geometry and size. A few preliminary results will be presented in this report.

The experimental set-up is like the one presented in the interim report, based on a pseudospark-like system without inner bore holes with proper preionisation [10]. It uses the basic principle of the superposition of two discharges; the main one being established by applying high-voltage pulses between an open hollow cathode and an anode, and the auxiliary one creating a preliminary plasma in the cathodic region. The possibility of operating at repetition rates up to 700 Hz has been shown [11]. Typical parameters of the electron beam produced in our discharge configuration [12] are summarized in the table below:

Mean electron energy (0.6-0.76 of maximum applied voltage)	17.5 keV
FWHM of energy spectrum (0.4 of ME)	7 keV
Temporal width of the fast electron beam	10 ns
Temporal width of the beam	14 ns
Minimum beam diameter (from anodic target damage)	50 μm
Maximum beam current (~ 0.1 of maximum discharge current)	65 A

The lack of inner diaphragms allowed the beam to be deflected using a magnetic field provided by external coils, while keeping the focusing properties on the anode target. This was proved by the X-ray emission from the scanning point-like source thus obtained which have been monitored by autoradiography [13]. We suppose that electrons are deflected inside the cathode at low velocities during the generation of the beam, and then are accelerated at the potential applied to the cathode-anode gap. In this way it is possible to control the coupling of the beam with different targets inside the discharge tube.

The X-rays were recorded by a collimated NE102A plastic scintillator, mounted outside the discharge tube, coupled via an optical fiber to a fast photomultiplier and an Tektronix TDS350 oscilloscope. Previous observations [5] have been confirmed, namely: the X-ray emission is associated with the electron beam "dressing" the dielectric fiber and the appearance of "hot points" on its surface, and the amplitude and the duration of the X-ray pulse does not depend on the discharge repetition rate in the investigated range (up to 100 Hz).

Several types of ferrite, as well as silicon oil and lithium niobate have been studied. It has been found that the degree of "cruising" of the electron beam depends on the ferrite composition. Besides the common cylindrical geometry using thin dielectric fibers, a quasi-planar geometry has been achieved using a low conductivity ferrite cylinder of 4 mm diameter

parallel to the discharge tube axis. Under proper preionization conditions, a 2 cm long filamentary discharge stabilized along the cylinder surface, associated with X-ray emission. Since no damage of the ferrite surface has been observed, apparently CE provides a mechanism of X-ray generation different of that proposed in [14], a mechanism in which the preionization of the gas adjacent to the dielectric surface plays a critical role for the "cruising" effect. Indeed, we observed the CE on dielectrics of various shapes and sizes, including submillimetric ferrite particles, and also with various geometries of the discharge; in all cases the preionization of the discharge gas was a necessary condition.

The amplitude of the X-ray pulse emitted by CE along 2 cm of ferrite has been found only about 10% less than that of the X-rays emitted by the discharge electron beam totally stopped in a stainless steel anode at 45° relative to the beam axis. This comparison proves that X-rays are also effectively generated by fast electrons in glancing interactions along the dielectric surface, however with smaller absorption losses.

We anticipate that for a dielectric fiber as target, provided a proper plasma (laser or discharge plasma) is generated on the cruising surface the CE would work also for relativistic electrons. In this case the X-ray emission by bremsstrahlung is main concentrated along the dielectric fiber inside a cone with an opening angle of $2/\gamma$ (where γ is the relativistic factor for the fast electrons in the beam).

Under certain conditions, a dielectric fiber containing nuclear isomers such $^{178}\text{Hf}^{m2}$ may become active medium for gamma ray emission. An X ray generator based on the scheme proposed in this work may provide an optimum coupling of the radiation to the active medium. More specifically, assuming that the nuclear isomers are concentrated along the center of the fiber and the X rays are generated around the fiber, the radiation power density at the isomers is inversely proportional to the radius of the (cylindrical) emitting surface. This hopefully would pave the way towards filamentary hard X-ray pumping sources strongly coupled with the irradiated active media, as requested for induced gamma emission. Accordingly, for the future our research will be devoted to investigate the CE on multilayer dielectric targets at higher electron beam densities and energies.

References

- [1] C. B. Collins and J. J. Carroll, "Progress in the pumping of gamma-ray laser", *Hyper.Inter.* **107**, 3 (1997)
- [2] M.Ganciu, G.Modreanu, A.M.Pointu, I.I.Popescu, "Generation of intense pulsed electron beams by superposition of two discharges" *J.Phys.D.-Appl. Phys.* **27**, 1370 (1994)
- [3] M.Ganciu, A. M. Pointu, I. I. Popescu, N. B. Mandache, V. Zoran, "Pulsed electron beams in transient plasmas", *Rom. Journ. Phys.*, **40**, 673 (1995)
- [4] M.Ganciu, E. Dewald, M. Nistor, D. Penache, I. I. Popescu, V. Zoran, "Surface guided electron beams on dielectric fibers (the cruise effect)" *Rom.Journ.Phys.* **39**, 787 (1994)
- [5] V. I. Zoran, M.Ganciu, A. M. Pointu, C. B. Collins and I.-Iovitz Popescu, "X-ray generation in inverse capillary discharges for pumping", *Hyper. Inter.*, **107**, 415 (1997)
- [6] Shigeo Kawata, Shigeru Kato, Susumi Hanamori, Shinichi Nishiyama, Kenta Naito and Musuhi Hakoda, "Effect of plasma generation at insulator surface on transport of intense electron beam through an insulator beam guide", *Jpn. J. Appl. Phys.*, **35**, 1127 (1996)
- [7] M.Ganciu, I. I. Popescu, V. Zoran, A. M. Pointu, "A high density pulsed ion trap", *Nucl. Instr. and Method in Phys. Res. B* **98**, 541 (1995)
- [8] E. Dewald, K. Frank, D.H.H. Hoffmann, R. Stark, M.Ganciu, N. B. Mandache, M. Nistor, A.M. Pointu, I.I. Popescu, "Pulsed intense electron beams generated in transient hollow cathode discharges: fundamentals and applications", *IEEE Trans. Plasma Sci.* (Special Issue, April 1997)

- [9] E. Dewald, M.Ganciu, N. B. Mandache, G. Musa, M. Nistor, A.M. Pointu, I.I. Popescu, K. Frank, D.H.H. Hoffmann, R. Stark , "The role of multielectrode geometry in generation of pulsed electron beams in preionization controlled open ended hollow cathode transient discharges", IEEE Trans. Plasma Sci. (Special Issue, April 1997)
- [10] M.Ganciu, A.M. Pointu, N.B. Mandache, I. Iovitz Popescu, "On the influence of cathode geometry upon electron beams produced by preionization controlled pseudospark-like discharges", SPIE, **2461**, 40 (1995)
- [11] Mircea Udrea, Mihaela Stoica, Irina Buica, Catalin Flacau, Anne-Marie Pointu, Mihai Ganciu, Dan Penache, Ioan-Iovitz Popescu, "High repetition rate operation of a double discharge electron beam generator", Opt. Eng., **35**, 1330 (1996)
- [12] N.B. Mandache, A.M. Pointu, E. Dewald, M. Nistor, M.Ganciu, G. Musa, I.I. Popescu, "The characterization of preionization controlled electron beams produced in open ended hollow cathode transient discharges", Plasma Sources Sci. and Technol. **6**, 1 (1997)
- [13] D. Penache, M.C. Penache, M. Nistor, H. Grecu, M. Ganciu, A.M. Pointu, M. Skovronek, I.I. Popescu, V. Zoran, "A scanning point-like X-ray source using transient hollow cathode discharges", X rays and Inner shell processes, 9-13 september 1996, Hambourg.
- [14] K. Watanabe, K. Furusho, S. Kashiwabara and R. Fujimoto, "Characteristics of X-ray radiation by a nonequilibrium energetic electron flow emerged from a formed ferrite filament" J.Appl.Phys. **68**, 5059 (1990)